WELLS LAMONT

Industrial

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style: Y9279

Overedge Size Part # Sizing:

XSmall Y9279XS Yellow Small Y9279S Red Medium Y9279M Green Y9279L Large Brown XLarge Y9279XL Navv Blue

Y9279XXL

XXLarge

Registered Brand Name: FlexTech™ Classification: Palm Dip



PRODUCT DESCRIPTION

Black

Description: Seamless Gray Polyester Palm Coated Glove

Color: Gray Shell / Gray Palm

Shell: Synthetic Knit Palm Coating: Polyurethane

Dozen Pair Sold by: Packaging (Inner Pack): 12 Pairs Packaging (Case Pack): 144 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F2992-15 Test Results: 271 grams

ANSI Level A1

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3389-10

Test Results: ANSI Level 3, 2340 Cycles

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pretreat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

This glove does not contain cut resistant materials. Do not use in conditions where cut protection is needed.

MARNING: Cancer – www.P65Warnings.ca.gov

Wells Lamont Industrial

Toll-Free 1.800.247.3295 www.wellslamontindustrial.com