

**PRODUCT SPECIFICATION SHEET****PRODUCT INFORMATION**

|                               |               |               |                 |
|-------------------------------|---------------|---------------|-----------------|
| <b>Style:</b>                 | <b>I2449T</b> |               |                 |
| <b>Sizing:</b>                | <u>Size</u>   | <u>Part #</u> | <u>Overedge</u> |
|                               | Medium        | I2449TM       | Green           |
|                               | Large         | I2449TL       | Brown           |
|                               | XLarge        | I2449TXL      | Navy Blue       |
|                               | XXLarge       | I2449TXXL     | Black           |
| <b>Registered Brand Name:</b> | FlexTech™     |               |                 |
| <b>Classification:</b>        | Impact        |               |                 |

**PRODUCT DESCRIPTION**

|                                |  |
|--------------------------------|--|
| <b>Description:</b>            | Seamless Knit Palm Coated Glove with Impact Pads |
| <b>Color:</b>                  | Hi-Vis Yellow Shell / Black Palm / Orange TPR    |
| <b>Shell:</b>                  | Blend of High Performance Fibers                 |
| <b>Lining:</b>                 | Brushed Fleece                                   |
| <b>Palm Coating:</b>           | Sandy Nitrile                                    |
| <b>Sold by:</b>                | Dozen Pair                                       |
| <b>Packaging (Inner Pack):</b> | 12 Pairs   |
| <b>Packaging (Case Pack):</b>  | 72 Pairs   |

**CUT PROTECTION PERFORMANCE INFORMATION**

|                      |                             |
|----------------------|-----------------------------|
| <b>Test Method:</b>  | ASTM F2992-15               |
| <b>Test Results:</b> | 1542 grams<br>ANSI Level A4 |

**ABRASION PROTECTION PERFORMANCE INFORMATION**

|                      |                          |
|----------------------|--------------------------|
| <b>Test Method:</b>  | ASTM D3884-10            |
| <b>Test Results:</b> | ANSI Level 4 9769 cycles |

**IMPACT PROTECTION PERFORMANCE INFORMATION**

|                      |                    |
|----------------------|--------------------|
| <b>Test Method:</b>  | ANSI/ISEA 138-2019 |
| <b>Test Results:</b> | ANSI Level 1       |

**CE EN 388 STANDARD**

|                                |       |         |
|--------------------------------|-------|---------|
| <b>EN Abrasion Resistance:</b> | § 6.1 | Level 4 |
| <b>EN Cut Resistance:</b>      | § 6.2 | Level 5 |
| <b>EN Tear Resistance:</b>     | § 6.3 | Level 4 |
| <b>EN Puncture Resistance:</b> | § 6.4 | Level 2 |

**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.