

**PRODUCT SPECIFICATION SHEET**

**PRODUCT INFORMATION**

<b>Style:</b>	<b>Y9214</b>		
<b>Sizing:</b>	<b>Size</b>	<b>Part #</b>	<b>Overedge</b>
	XSmall	Y9214XS	Yellow
	Small	Y9214S	Red
	Medium	Y9214M	Green
	Large	Y9214L	Brown
	XLarge	Y9214XL	Navy Blue
	XXLarge	Y9214XXL	Black
<b>Registered Brand Name:</b>	FlexTech™		
<b>Classification:</b>	Palm Dip		



**PRODUCT DESCRIPTION**

<b>Description:</b>	Cut Resistant Sandy Nitrile Palm Coated Touchscreen Gloves
<b>Color:</b>	Gray Shell / Black Palm
<b>Material:</b>	13 Gauge HPPE; Silicone-Free; Latex-Free
<b>Coating:</b>	Sandy Nitrile
<b>Sold by:</b>	Dozen Pair
<b>Packaging (Inner Pack):</b>	12 Pair
<b>Packaging (Case Pack):</b>	144 Pair

**CUT PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM F2992-15
<b>Test Results:</b>	ANSI Level A6

**ABRASION PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM D3389-10
<b>Test Results:</b>	ANSI Level 4 >3,000 Cycles

**PUNCTURE PERFORMANCE INFORMATION**

<b>Test Method:</b>	EN388:2003
<b>Test Results:</b>	121N
<b>ANSI Level:</b>	4

**CE EN 388 STANDARD**

<b>Test Method:</b>	EN388: 2016
<b>Test Results:</b>	
<b>EN Abrasion Resistance:</b>	Level 4
<b>EN Cut Resistance (Coup):</b>	Level X
<b>EN Tear Resistance:</b>	Level 4
<b>EN Puncture Resistance:</b>	Level 4
<b>EN Cut Resistance (TDM):</b>	Level F

**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.