

PRODUCT INFORMATION

Style:	Y9215		
Sizing:	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	XSmall	Y9215XS	Yellow
	Small	Y9215S	Red
	Medium	Y9215M	Green
	Large	Y9215L	Brown
	XLarge	Y9215XL	Navy Blue
	XXLarge	Y9215XXL	Black
Registered Brand Name:	FlexTech™		
Classification:	Palm Dip		



PRODUCT DESCRIPTION

Description:	Cut Resistant PU Palm Coated Touchscreen Gloves
Color:	Gray Shell / Black Palm
Material:	13 Gauge HPPE; Silicone-Free; Latex-Free
Coating:	Polyurethane
Sold by:	Dozen Pair
Packaging (Inner Pack):	12 Pair
Packaging (Case Pack):	144 Pair

CUT PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM F2992-15
Test Results:	ANSI Level A6

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM D3389-10
Test Results:	ANSI Level 4 >3,000 Cycles

PUNCTURE PERFORMANCE INFORMATION

Test Method:	EN388:2003
Test Results:	93N
ANSI Level:	3

CE EN 388 STANDARD

Test Method:	EN388: 2016
Test Results:	
EN Abrasion Resistance:	Level 4
EN Cut Resistance (Coup):	Level X
EN Tear Resistance:	Level 4
EN Puncture Resistance:	Level 3
EN Cut Resistance (TDM):	Level F

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.