

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style:	Kevlar Standard Sleeve		
Sizing:	<u>Size</u>	<u>Part #</u>	
		<u>Standard</u>	<u>Thumb Hole</u>
	10"	SK-10	
	14"	SK-14	SK-14H
	16"	SK-16	
	18"	SK-18	SK-18H
	24"	SK-24	SK-24H
Classification:	Cut Resistant		



PRODUCT DESCRIPTION

Description:	Kevlar® Standard Sleeve
Color:	Yellow
Material:	100% Kevlar (2-ply knit)
Wrist:	With or Without a Thumb Hole
Packaging (Inner Pack):	12 Pieces
Packaging (Case Pack):	288 Pieces

CUT PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM F1790-97
Test Results:	1207 grams / 2.66lbs. ANSI Level 3
Test Method:	ASTM F2992-15
Test Results:	1257 grams ANSI Level A3

FLAME TESTING INFORMATION

Test Method:	ASTM F1358-08
Test Results:	ANSI Level 4

HEAT TESTING INFORMATION

Test Method:	ASTM F1060-08
Test Results:	350°F Heat Resistance ANSI Level 2 Heat Rating

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM D3884-05
Test Results:	388 revs (cycles)

WASHING INSTRUCTIONS

Remove all large particles. Rinse with cold water then machine wash in warm water with mild detergent or soap for 10-15 minutes. Water temperature should not exceed 160°F (71°C). Rinse in cold water. Tumble dry for 10-15 minutes, not exceeding 150°F (67°C). Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

