

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style: Cut Resistant Sleeve

Sizing:

<u>Size</u>	<u>Part #</u>
	<u>Standard</u>
22"	5600SLV-22

Classification: Cut Resistant



PRODUCT DESCRIPTION

Description: 15g Cut Resistant Sleeve (CFR 21 - Approved for Food Contact)

Color: Blue

Shell: Combination of high performance, durable fibers and wire
CFR 21 - Approved for Food Contact

Sold by: Dozen Pieces

Packaging (Inner Pack): 6 Pieces

Packaging (Case Pack): 48 Pieces

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F2992-15

Test Results: 4,678 grams

ANSI Level: A7

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-09

Test Results: ANSI Level 2, 774 Cycles

PUNCTURE PERFORMANCE INFORMATION

Test Method: EN388:2003

Test Results: 64N

ANSI Level: 3

WASHING INSTRUCTIONS

Remove all large particles. Rinse with cold water then machine wash in warm water with mild detergent or soap for 10-15 minutes. Water temperature should not exceed 160°F (71°C). Rinse in cold water. Tumble dry for 10-15 minutes, not exceeding 150°F (67°C). A diluted bleach solution may be used (5.25% sodium hypochlorite or 1:10 household bleach).

CAUTION

Sleeves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial

Toll-Free 1.800.247.3295 www.wellslamontindustrial.com