

PRODUCT INFORMATION

Style:	Y9275		
Sizing:	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	XSmall	Y9275XS	Yellow
	Small	Y9275S	Red
	Medium	Y9275M	Green
	Large	Y9275L	Brown
	XLarge	Y9275XL	Navy Blue
	XXLarge	Y9275XXL	Black
Registered Brand Name:	FlexTech™		
Classification:	Palm Dip		



PRODUCT DESCRIPTION

Description:	High Performance Polyethylene Fiber (HPPE) Palm Coated Seamless Glove
Color:	Speckled Gray Shell / Grey Palm
Shell:	High Performance Polyethylene (HPPE)/Polyester/Spandex
Palm Coating:	Polyurethane
Sold by:	Dozen Pair
Packaging (Inner Pack):	12 Pairs
Packaging (Case Pack):	144 Pairs

CUT PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM F1790-97
Test Results:	522 grams / 1.15 lbs ANSI Cut Level 2
Test Method:	ASTM F2992-15
Test Results:	526 grams ANSI Level A2

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method:	ASTM D3389-10
Test Results:	ANSI Level 6 22,400 Cycles

PUNCTURE PERFORMANCE INFORMATION

Test Method:	EN388:2003
Test Results:	75N
ANSI Level:	3

CE EN 388 STANDARD

EN Abrasion Resistance:	§6.1	Level 4
EN Cut Resistance:	§6.2	Level 3
EN Tear Resistance:	§6.3	Level 4
EN Puncture Resistance:	§6.4	Level 2

WASHING INSTRUCTIONS

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

⚠WARNING: Cancer - www.P65Warnings.ca.gov